# Minilator<sup>TM</sup>



The LSP Minilator is a simple to operate constant flow device which provides oxygen for up to five patients simultaneously.

The versatile Minilator features 50 psig outlets, which can be used to operate a demand resuscitator valve, suction device, CPAP mask, or ventilator. All five oxygen outlets can function simultaneously, supplying 40 to 90 psig or low flow oxygen. Threaded barbed fittings with metered orifices can be fitted to the DISS check valves to provide consistent accurate flow rates of 4, 6, 10 or 15 liters per minute. Using standard DISS outlets, the Minilator is easily attached to an oxygen source via standard oxygen hoses and/or connectors. The zippered nylon carry case keeps the components clean and stores them fully assembled and ready for use.

#### **Standard Features**

- Expandable ... Minilators can be connected in tandem for emergency or mass casualty situations where more than five oxygen outlets are required.
- Durable ... anodized aluminum construction will withstand harsh weather conditions and corrosive materials.
- Compact and lightweight ... low-profile design for easy storage.



## Minilator<sup>TM</sup>

### **SPECIFICATIONS**

Supply Pressure: 40-90 psig

**Operating Temperature:** -30° F to 125° F **Storage Temperature:** -40° F to 160° F

Flow Rates: 4, 6, 10 or 15 lpm, depending on orifice

Materials: manifold - anodized aluminum;

fittings - plated brass; barbs - H.I. polystyrene; orifices - stainless steel

Weight: 13.5 oz.

**Dimensions:** 1" x 3" x 6" without barbs

1" x 6" x 7-1/2" with barbs attached

### ORDERING INFORMATION

**L419-010** Minilator: 4" aluminum manifold with five oxygen DISS check valves, five screw-on 4 lpm orifices, zippered nylon carry case

L419-020 Minilator, same as L419-010 but with five 6 lpm orifices
L419-030 Minilator, same as L419-010 but with five 10 lpm orifices
L419-050 Minilator, same as L419-010 but with five 15 lpm orifices

 L419
 Minilator, 4" manifold only

 L555005
 Orifice, 2 lpm, 5/pkg

 L555006
 Orifice, 4 lpm, 5/pkg.

 L555007
 Orifice, 6 lpm, 5/pkg.

 L555008
 Orifice, 10 lpm, 5/pkg.







EMERGO EUROPE Prinsessegracht 20 2514 AP The Hague The Netherlands



Allied Healthcare Products, Inc. • 1720 Sublette Avenue • St. Louis, MO 63110 USA 314/771-2400 • 800/444-3954 • FAX: 314/771-0650 • www.alliedhpi.com

U.S. Toll Free: 800/444-3940 FAX: 800/477-7701 Canada & Mexico Toll Free: 800/446-0552 FAX: 800/246-6201 International Telephone: 314/268-1683 FAX: 314/771-5183