

Geometrically Keyed Medical Gas Outlets

Elements

- Safety keyed to prevent gas cross connections
- Conforms to NFPA 99 and CGA standards
- Built-in push-button latch release mechanism
- Modular design
- Cleaned for oxygen service
- UL listed





Description

The Chemetron® 550 Series outlet stations provide convenient access to medical gases in patient care locations. They are fully compatible with Puritan Bennett style geometrically keyed adapters.

The outlets are field-gangable in any order desired by the facility. Outlets are spaced 5" (12.7 cm) center to center, and may be ganged with Chemetron modular electrical assemblies in a console arrangement. Outlet finish plates and rough-in plates are pin indexed using steel pins for positive cross-connection prevention. Primary valves are separate from the finish plate, allowing easy testing for leaks and cross connection. Primary valves are made of brass and contain a chrome-plated self-sealing poppet. Primary valves are field-adjustable to compensate for variations in plaster thickness of 1/2" to 3/4".

The type K copper inlet tube has a 1/2" OD connection, and can rotate 360 degrees to accommodate any field piping arrangement. The primary gas check can be serviced without shutting off the gas supply.





The outlet stations are fully compliant with NFPA 99 and are cleaned for oxygen service in accordance with CGA G-4.1. The outlet is UL listed. Gas identification is provided by a polycarbonate plastic insert, color coded by gas service.


The latch release is color-coded and labeled for the gas service. Release is easily accomplished with one hand using a push-button release. The primary valve poppet provides a dust-proof seal. Vacuum outlets may be used with or without slide brackets for vacuum collection bottles of up to 1/2-gallon capacity. (Where slide brackets are used, order one per vacuum outlet.)

Ordering Information

Gas Service	Catalog Number U.S. Color Codes	Quantity
Oxygen	64-03-5001	
Vacuum	64-03-5002	
Air	64-03-5003	
Nitrous Oxide	64-03-5004	
Evacuation Vacuum	64-03-5006	
Slide Bracket	64-06-0001	



Dimensional Data



Refer to installation instruction prior to assembly.





All specifications are nominal and subject to change without notice.

Warranty:

See Allied Statement of Warranties for details.

© 2005 Allied Healthcare Products, Inc.® Printed in USA

Customer Service:

USA: (800) 444-3960 FAX: (314) 771-7537

Canada/Mexico: (800) 446-0552

FAX: (800) 246-6201

International: (314) 268-1683 FAX: (314) 771-5183

Allied HEALTHCARE PRODUCTS INC

1720 Sublette Avenue St. Louis, MO 63110 USA (314)771-2400 www.alliedhpi.com ISO 9001 CERTIFIED

Product Specification